



| PT NO | COMPONENT DESCRIPTION | N. S. (INS) | CLASS | QTY |
|----------|---|----------------|-------|------|
| | PIPE | | | |
| 1 | PIPE;SEAMLESS;;BE;;ASME B36.10 API 5L;GR.B OR ASTM A106;GR.B;NACE MR0175; STD | 2 | B | 0.3M |

| | | | | |
|---|---|---|---|---|
| 2 | ELBOW;90DEG.LR;SEAMLESS;BW;;ASME B16.9 ASTM A234;GR.WPB;NACE MR0175; STD | 2 | B | 1 |
|---|---|---|---|---|

| | | | | |
|---|---|---|---|---|
| 3 | FLANGE;;WN;RF;300#;ASME B16.5;SMOOTH FINISH RA 3.2 TO 6.3 MICRONS ASTM A105;NACE MR0175;; STD | 2 | B | 1 |
|---|---|---|---|---|

| PT NO | COMPONENT DESCRIPTION | N.S. (INS) | CLASS | QTY |
|----------|-----------------------|---------------|-------|-----|
|----------|-----------------------|---------------|-------|-----|

| | | | | |
|---|---|---|---|---|
| 4 | GASKET;SPIRAL WOUND;4.4MM THK;300#;ASME B16.20 WND:SS316;FLR:GRAPHITE;INNER & OUTER GUIDE RINGS:SS316;NACE MR0175 | 2 | B | 2 |
|---|---|---|---|---|

| | | | | |
|---|--|-----|---|----|
| 5 | 90 STUD BOLT WITH HEAVY HEX. NUTS STUDS: ASTM A193-B7, NUTS: ASTM A194-2H FLUOROCARBON COATED WITH AMERI-COTE OR APPROVED EQUAL | 5/8 | B | 16 |
|---|--|-----|---|----|

| | | | | |
|---|---|---|---|---|
| 6 | VALVE; BALL; RB; FLANGED; RF; 300#; ; DATASHEET: B2R | 2 | B | 1 |
|---|---|---|---|---|

[illegible]