



CONT. ON
CD-2"-PG-F-1054-P
E 90816
N 101100
FI +24107

PT NO	COMPONENT DESCRIPTION	N.S. (INS)	CLASS	QTY
<u>PIPE</u>				
1	PIPE;SEAMLESS;;BE;;ASME B36.10 API 5L;GR.B OR ASTM A106;GR.B;NACE MR0175; SCHXXS	2	F	3.7M
<u>FITTINGS</u>				
2	ELBOW;90DEG.LR;SEAMLESS;BW;;ASME B16.9 ASTM A234;GR.WPB;NACE MR0175; SCHXXS	2	F	3
<u>FLANGES</u>				
3	FLANGE;WN;;RTJ;1500#;ASME B16.5 ASTM A105;NACE MR0175;; SCHXXS	2	F	3
<u>VALVES / IN-LINE ITEMS</u>				
4	VALVE;CHECK;SWING;FLANGED;RTJ;1500#; ;DATASHEET:F5J	2	F	1
5	VALVE;BALL;RB;FLANGED;RTJ;1500#; ;DATASHEET:F2J	2	F	1

PT NO	COMPONENT DESCRIPTION	N.S. (INS)	CLASS	QTY
	<u>GASKETS</u>			
6	GASKET;OVAL RING;;1500#;ASME B16.20 SOFT IRON;ELECTROZINC PLATED;MAX. BHN 90;NACE MRO175	2	F	4
	<u>BOLTS</u>			
7	145 STUD BOLT WITH HEAVY HEX. NUTS STUDS: ASTM A193-B7, NUTS: ASTM A194-2H FLUOROCARBON COATED WITH AMERI-COTE OR APPROVED EQUAL	7/8	F.	32
	<u>SUPPORTS</u>			
8	PIPE SHOE PS04-50-2-A	2	-	1
9	RIGHT ANGLE SUPPORT PS30-07-05	2	-	1
10	PIPE SHOE - SLOPING LINES PS05-50-A-100	2	-	1
11	PIPE SHOE GUIDE PS07-50-3	2	-	1
12	INVERTED RIGHT ANGLE SUPPORT PS29-05-06	2	-	1

[illegible]